

POLY MAX WHEELS



Features

- High Strength Urethane Tread
- Autoclave Safe
- Resists Chemical Absorption
- Hardness is 90A
- High Performance
- Temp Range (-40F to +180F)
- Standard Tread Color is Blue

Options

- Precision, Roller, and Delrin Bearings Available
- Alternative Colors Available

Poly Max Wheels

Wheel Dia. (in.)	Tread Width (in.)	Load Rating (lbs.)	Hub Length (in.)	Axle Size Without Bearing	Axle Size Bearing & No Spanner	Axle Size Bearing & Spanner	Bearing	Description	Order No.
3	1 1/4	225	1 11/16	-	3/8	-	Precision	WHL-30-125-PM3	70824
	1 1/4	225	1 11/16	-	3/8	-	Delrin	WHL-30-125-PM1	70823
3 1/2	1 1/4	250	1 11/16	-	3/8	-	Precision	WHL-35-125-PM3	70826
	1 1/4	250	1 11/16	-	3/8	-	Delrin	WHL-35-125-PM1	70825
4	1 1/4	300	1 11/16	-	3/8	-	Precision	WHL-40-125-PM3	70828
	1 1/4	300	1 11/16	-	3/8	-	Delrin	WHL-40-125-PM1	70827
	2	600	2 3/16	1 3/16	-	-	Plain	WHL-40-200-PM0	70800
	2	600	2 3/16	-	3/4	1/2	Delrin	WHL-40-200-PM1	70801
	2	600	2 3/16	-	3/4	1/2	Roller	WHL-40-200-PM2	70802
	2	600	2 3/16	-	-	1/2	Precision	WHL-40-200-PM3	70803
5	1 1/4	325	1 11/16	-	3/8	-	Precision	WHL-50-125-PM3	70830
	1 1/4	325	1 11/16	-	3/8	-	Delrin	WHL-50-125-PM1	70829
	2	900	2 3/16	1 3/16	-	-	Plain	WHL-50-200-PM0	70804
	2	900	2 3/16	-	3/4	1/2	Delrin	WHL-50-200-PM1	70805
	2	900	2 3/16	-	3/4	1/2	Roller	WHL-50-200-PM2	70806
	2	900	2 3/16	-	-	1/2	Precision	WHL-50-200-PM3	70807
6	2	1100	2 3/16	1 3/16	-	-	Plain	WHL-60-200-PM0	70808
	2	1100	2 3/16	-	3/4	1/2	Delrin	WHL-60-200-PM1	70809
	2	1100	2 3/16	-	3/4	1/2	Roller	WHL-60-200-PM2	70810
	2	1100	2 3/16	-	-	1/2	Precision	WHL-60-200-PM3	70811
8	2	1200	2 3/16	1 3/16	-	-	Plain	WHL-80-200-PM0	70812
	2	1200	2 3/16	-	3/4	1/2	Delrin	WHL-80-200-PM1	70813
	2	1200	2 3/16	-	3/4	1/2	Roller	WHL-80-200-PM2	70814
	2	1200	2 3/16	-	-	1/2	Precision	WHL-80-200-PM3	70815