

SOLID URETHANE WHEELS



Features

- High Load Capacity
- Resists Chemical Absorption
- Hardness is 55D
- High Performance
- Solid Wheel – No Tread Separation
- Temp Range (-50F to +180F)
- Standard Color is Blue

Options

- Precision, Roller, and Delrin Bearings Available
- Alternative Colors Available

Solid Urethane Wheels

Wheel Dia. (in.)	Tread Width (in.)	Load Rating (lbs.)	Hub Length (in.)	Axle Size Without Bearing	Axle Size Bearing & No Spanner	Axle Size Bearing & Spanner	Bearing	Description	Order No.
3	1 1/4	300	1 9/16	1/2	-	-	Plain	WHL-30-125-SU0	70215
4	1 1/4	500	1 9/16	1/2	-	-	Plain	WHL-40-125-SU0	70216
	2	700	2 3/16	1 3/16	-	-	Plain	WHL-40-200-SU0	70238
	2	700	2 3/16	-	3/4	1/2	Delrin	WHL-40-200-SU1	70218
	2	700	2 3/16	-	-	1/2	Precision	WHL-40-200-SU3	70220
5	1 1/4	700	1 9/16	1/2	-	-	Plain	WHL-50-125-SU0	70221
	2	1000	2 3/16	1 3/16	-	-	Plain	WHL-50-200-SU0	70239
	2	1000	2 3/16	-	3/4	1/2	Delrin	WHL-50-200-SU1	70223
	2	1000	2 3/16	-	-	1/2	Precision	WHL-50-200-SU3	70225
6	2	1200	2 3/16	1 3/16	-	-	Plain	WHL-60-200-SU0	70240
	2	1200	2 3/16	-	3/4	1/2	Delrin	WHL-60-200-SU1	70227
	2	1200	2 3/16	-	-	1/2	Precision	WHL-60-200-SU3	70229
8	2	1500	2 3/16	1 3/16	-	-	Plain	WHL-80-200-SU0	70230
	2	1500	2 3/16	-	3/4	1/2	Delrin	WHL-80-200-SU1	70231
	2	1500	2 3/16	-	-	1/2	Precision	WHL-80-200-SU3	70233