

# GLASS FILLED POLYPROPYLENE WHEELS

## Features

- High Load Capacity
- Water Resistant
- Resists Chemical Absorption
- Hardness is 65D
- High Performance
- Cost Effective
- Temp Range (-20F to +250F)

## Options

- Precision, Roller, and Delrin Bearings Available
- HT Version Available in Brown Color (-20F to +480F)



**WHEELS**

## Glass Filled Polypropylene Wheels

Wheel Dia. (in.)	Tread Width (in.)	Load Rating (lbs.)	Hub Length (in.)	Axle Size Without Bearing	Axle Size Bearing & Spanner	Bearing	Description	Order No.
<b>3 1/2</b>	1 1/2	600	1 9/16	1 3/16	-	Plain	WHL-35-150-GFP0	70600
	1 1/2	600	1 9/16	1/2	-	Plain	WHL-35-150-GFP0	70601
	1 1/2	600	1 9/16	3/8	-	Plain	WHL-35-150-GFP0	70602
<b>4</b>	1 1/2	700	1 9/16	1 3/16	-	Plain	WHL-40-150-GFP0	70605
	1 1/2	700	1 9/16	3/4	-	Plain	WHL-40-150-GFP0	70606
	1 1/2	700	1 9/16	1/2	-	Plain	WHL-40-150-GFP0	70607
	1 1/2	700	1 9/16	3/8	-	Plain	WHL-40-150-GFP0	70608
	2	800	2 3/16	1 3/16	-	Plain	WHL-40-200-GFP0	70611
	2	800	2 3/16	3/4	1/2	Delrin	WHL-40-200-GFP1	70632B
	2	800	2 3/16	3/4	1/2	Roller	WHL-40-200-GFP2	70613
	2	800	2 3/16	-	1/2	Precision	WHL-40-200-GFP3	70614
<b>5</b>	1 1/2	800	1 9/16	1 3/16	-	Plain	WHL-50-150-GFP0	70615
	1 1/2	800	1 9/16	1/2	-	Plain	WHL-50-150-GFP0	70616
	1 1/2	800	1 9/16	3/8	-	Plain	WHL-50-150-GFP0	70617
	2	1000	2 3/16	1 3/16	-	Plain	WHL-50-200-GFP0	70620
	2	1000	2 3/16	3/4	1/2	Delrin	WHL-50-200-GFP1	70633B
	2	1000	2 3/16	3/4	1/2	Roller	WHL-50-200-GFP2	70622
	2	1000	2 3/16	-	1/2	Precision	WHL-50-200-GFP3	70623
	<b>6</b>	2	1200	2 3/16	1 3/16	-	Plain	WHL-60-200-GFP0
2		1200	2 3/16	3/4	1/2	Delrin	WHL-60-200-GFP1	70634B
2		1200	2 3/16	3/4	1/2	Roller	WHL-60-200-GFP2	70626
2		1200	2 3/16	-	1/2	Precision	WHL-60-200-GFP3	70627
<b>8</b>	2	1400	2 3/16	1 3/16	-	Plain	WHL-80-200-GFP0	70628
	2	1400	2 3/16	3/4	1/2	Delrin	WHL-80-200-GFP1	70635B
	2	1400	2 3/16	3/4	1/2	Roller	WHL-80-200-GFP2	70630
	2	1400	2 3/16	-	1/2	Precision	WHL-80-200-GFP3	70631