

HT GLASS FILLED POLYPROPYLENE WHEELS



Features

- High Temperature Material
- Water Resistant
- Resists Chemical Absorption
- Hardness is 65D
- Standard Color is Brown
- Temp Range (-20F to +480F)

Options

- Precision, Roller, and Delrin Bearings Available

WHEELS

HT Glass Filled Polypropylene Wheels

Wheel Dia. (in.)	Tread Width (in.)	Load Rating (lbs.)	Hub Length (in.)	Axle Size Without Bearing	Axle Size Bearing & Spanner	Bearing	Description	Order No.
3 1/2	1 1/2	600	1 9/16	1/2	-	Plain	WHL-35-150-GFP0 HT	70641
4	1 1/2	700	1 9/16	1/2	-	Plain	WHL-40-150-GFP0 HT	70644
	2	800	2 3/16	1 3/16	-	Plain	WHL-40-200-GFP0 HT	70646
	2	800	2 3/16	3/4	1/2	Delrin	WHL-40-200-GFP1 HT	70647
	2	800	2 3/16	3/4	1/2	Roller	WHL-40-200-GFP2 HT	70648
	2	800	2 3/16	-	1/2	Precision	WHL-40-200-GFP3 HT	70649
5	1 1/2	800	1 9/16	1/2	-	Plain	WHL-50-150-GFP0 HT	70651
	2	1000	2 3/16	1 3/16	-	Plain	WHL-50-200-GFP0 HT	70653
	2	1000	2 3/16	3/4	1/2	Delrin	WHL-50-200-GFP1 HT	70654
	2	1000	2 3/16	3/4	1/2	Roller	WHL-50-200-GFP2 HT	70655
	2	1000	2 3/16	-	1/2	Precision	WHL-50-200-GFP3 HT	70656
6	2	1200	2 3/16	1 3/16	-	Plain	WHL-60-200-GFP0 HT	70657
	2	1200	2 3/16	3/4	1/2	Delrin	WHL-60-200-GFP1 HT	70658
	2	1200	2 3/16	3/4	1/2	Roller	WHL-60-200-GFP2 HT	70659
	2	1200	2 3/16	-	1/2	Precision	WHL-60-200-GFP3 HT	70660
8	2	1400	2 3/16	1 3/16	-	Plain	WHL-80-200-GFP0 HT	70661
	2	1400	2 3/16	3/4	1/2	Delrin	WHL-80-200-GFP1 HT	70662
	2	1400	2 3/16	3/4	1/2	Roller	WHL-80-200-GFP2 HT	70663
	2	1400	2 3/16	-	1/2	Precision	WHL-80-200-GFP3 HT	70664