

MOLD ON RUBBER WHEELS

Features

- Cushioned Rubber Tread
- Cast Iron Core
- Hardness is 75A
- Quiet, Smooth Ride
- Temp Range (-40F to +180F)



Mold On Rubber Wheels

Wheel Dia. (in.)	Tread Width (in.)	Load Rating (lbs.)	Hub Length (in.)	Axle Size Without Bearing	Axle Size Bearing & No Spanner	Axle Size Bearing & Spanner	Bearing	Description	Order No.
4	2	380	2 3/16	1 3/16	-	-	Plain	WHL-40-200-MOR0	70400
	2	380	2 3/16	1 3/16	3/4	1/2	Roller	WHL-40-200-MOR2	70401
5	2	380	2 3/16	1 3/16	-	-	Plain	WHL-50-200-MOR0	70402
	2	380	2 3/16	1 3/16	3/4	1/2	Roller	WHL-50-200-MOR2	70403
6	2	420	2 3/16	1 3/16	-	-	Plain	WHL-60-200-MOR0	70404
	2	420	2 3/16	1 3/16	3/4	1/2	Roller	WHL-60-200-MOR2	70405
	2 1/2	600	2 7/8	1 3/16	-	-	Plain	WHL-60-250-MOR0	70406
	2 1/2	600	2 7/8	1 3/16	3/4	1/2	Roller	WHL-60-250-MOR2	70407
	2 1/2	600	3 1/4	1 15/16	-	-	Plain	WHL-60-250-MOR0	70408
	2 1/2	600	3 1/4	1 15/16	1	3/4	Roller	WHL-60-250-MOR2	70409
	3	700	3 1/4	1 15/16	-	-	Plain	WHL-60-300-MOR0	70410
	3	700	3 1/4	1 15/16	1	3/4	Roller	WHL-60-300-MOR2	70411
8	2	500	2 3/16	1 3/16	-	-	Plain	WHL-80-200-MOR0	70412
	2	500	2 3/16	1 3/16	3/4	1/2	Roller	WHL-80-200-MOR2	70413
	2 1/2	800	2 7/8	1 3/16	-	-	Plain	WHL-80-250-MOR0	70414
	2 1/2	800	2 7/8	1 3/16	3/4	1/2	Roller	WHL-80-250-MOR2	70415
	2 1/2	800	3 1/4	1 15/16	-	-	Plain	WHL-80-250-MOR0	70416
	2 1/2	800	3 1/4	1 15/16	1	3/4	Roller	WHL-80-250-MOR2	70417
	3	850	3 1/4	1 15/16	-	-	Plain	WHL-80-300-MOR0	70418
	3	850	3 1/4	1 15/16	1	3/4	Roller	WHL-80-300-MOR2	70419
10	2 1/2	900	2 7/8	1 3/16	-	-	Plain	WHL-100-250-MOR0	70422
	2 1/2	900	2 7/8	1 3/16	3/4	1/2	Roller	WHL-100-250-MOR2	70423
	2 1/2	800	3 1/4	1 15/16	1	3/4	Roller	WHL-100-250-MOR2	70424
	3	1000	3 1/4	1 15/16	-	-	Plain	WHL-100-300-MOR0	70425
	3	1000	3 1/4	1 15/16	1	3/4	Roller	WHL-100-300-MOR2	70426
12	2 1/2	900	3 1/4	1 13/16	1	3/4	Roller	WHL-120-250-MOR2	70427
	3	1150	3 1/4	1 15/16	-	-	Plain	WHL-120-300-MOR0	70428
	3	1150	3 1/4	1 15/16	1	3/4	Roller	WHL-120-300-MOR2	70429