

PHENOLIC WHEELS



Features

- High Load Capacity
- Resistant to Oil, Gasoline, and Dilute Acids
- Non-marking
- Hardness is 75D
- Temp Range -40F to 250F

Options

- Roller, Delrin and Precision Ball Bearing

Phenolic Wheels

Wheel Dia. (in.)	Tread Width (in.)	Load Rating (lbs.)	Hub Length (in.)	Axle Size Plain Bore	Axle Size Roller Bearing	Description	Order No.
3	1 1/4	300	1 9/16	1/2	3/4	WHL-30-125-PH0	70767
4	2	800	2 3/16	1 3/16	3/4	WHL-40-200-PH2	70758B
5	2	1000	2 3/16	1 3/16	3/4	WHL-50-200-PH2	70759B
6	2	1200	2 3/16	1 3/16	3/4	WHL-60-200-PH2	70760B
	2 1/2	1600	2 3/4	1 3/16	3/4	WHL-60-250-PH2	70771B
	3	2000	3 1/4	1 15/16	1	WHL-60-300-PH2	97392B
8	2	1400	2 3/16	1 3/16	3/4	WHL-80-200-PH2	70761B
	2 1/2	2000	2 3/4	1 3/16	3/4	WHL-80-250-PH2	70772B
	3	2500	3 1/4	1 15/16	1	WHL-80-300-PH2	97393B
10	2 1/2	2400	2 3/4	1 3/16	3/4	WHL-100-250-PH2	70773B
	3	2900	3 1/4	1 15/16	1	WHL-100-300-PH2	97394B
12	3	3500	3 1/4	1 15/16	1	WHL-120-300-PH2	97395B

OTHER SIZES AVAILABLE